

# Apollo 1500



## TECHNICAL SPECIFICATIONS

Country of Origin:	China	Colours:	12 Standard
Total Product Thickness:	6.5mm	Backing:	1.5mm Acoustic Backing
Hard Flooring Size:	180mm x 1500mm	Installation Method:	Uniclic®
Type:	Hybrid Flooring	Wear Layer:	0.5mm
Units Per Box:	6 boards	m <sup>2</sup> per box:	1.62
m <sup>2</sup> per pallet:	113.4	Finish:	Matte
Surface:	Embossed	Profile:	Micro Bevel
Substrate Layer:	Trigon® Core Technology (Limestone Composite)	Top Layer:	Decorative Film & Wear Layer
Protective Coating:	PUR & Scratch Resistance	Quickship AU:	Thredbo, Franklin, Pyrenees, Alpine Gum, Derwent, Blackbutt, Daintree, Spotted Gum, Boston, Midnight
Quickship QLD:	Thredbo, Franklin, Pyrenees, Alpine Gum, Derwent, Blackbutt, Daintree, Boston	Quickship WA:	Thredbo, Franklin, Pyrenees, Alpine Gum, Derwent, Blackbutt, Daintree, Spotted Gum, Sherbrooke, Cumberland, Boston, Midnight

## PERFORMANCE

Flammability:	(EN ISO 9239) CRF 10.9kW/m <sup>2</sup>
Colourfast to light:	(EN ISO 105-B02) Grade 6
Light Reflectance:	Available on Request
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 81% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: -0.00%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS/NZ 4586-2013) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide <a href="http://www.ghcommercial.com">www.ghcommercial.com</a>

## SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Micro Bevel Edge



Matte Finish



Mid Range



ISO 9001 Quality Management System



ISO 14001 Environment Management System



0.5mm Wear Layer

# Apollo 1500



Trigon Core Technology



Celebrating Australian Species



Waterproof Surface



Waterproof Core



Codemark Certified for Apollo Hybrid Flooring




Codemark Certified Waterproof


# Apollo 1500




105  
Thredbo



175  
Franklin




515  
Pyrenees




525  
Alpine Gum




535  
Derwent




545  
Blackbutt




551  
Daintree



556  
Spotted Gum



571  
Sherbrooke



721  
Cumberland



730  
Boston



790  
Midnight

# Apollo 1500



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.

\*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.