

Apollo 1500



TECHNICAL SPECIFICATIONS

Country of Origin:	China	Colours:	12 Standard
Total Product Thickness:	6.5mm	Backing:	1.5mm Acoustic Backing
Size:	180mm x 1500mm	Installation Method:	Uniclic®
Type:	Hybrid Flooring	Wear Layer:	0.5mm
Units Per Box:	6 boards	m ² per box:	1.62
m ² per pallet:	113.4	Finish:	Matte
Surface:	Embossed	Profile:	Micro Bevel
Substrate Layer:	Trigon® Core Technology (Limestone Composite)	Top Layer:	Decorative Film & Wear Layer
Protective Coating:	PUR & Scratch Resistance	Quickship AU:	Thredbo, Franklin, Pyrenees, Alpine Gum, Derwent, Blackbutt, Daintree, Spotted Gum, Boston, Midnight
Quickship QLD:	Thredbo, Franklin, Pyrenees, Alpine Gum, Derwent, Blackbutt, Daintree, Boston	Quickship WA:	Thredbo, Franklin, Pyrenees, Alpine Gum, Derwent, Blackbutt, Daintree, Spotted Gum, Sherbrooke, Cumberland, Boston, Midnight

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 10.9kW/m ²
Colourfast to light:	(EN ISO 105-B02) Grade 6
Light Reflectance:	Available on Request
Smoke Value:	(EN ISO 9239) 81% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: -0.00%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS/NZ 4586-2013) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Micro Bevel Edge



Matte Finish



Mid Range



ISO 9001 Quality Management System



ISO 14001 Environment Management System



0.5mm Wear Layer

Apollo 1500



Trigon Core Technology



Celebrating Australian Species



Waterproof Surface




Waterproof Core


Apollo 1500




105
Thredbo



175
Franklin




515
Pyrenees




525
Alpine Gum




535
Derwent




545
Blackbutt




551
Daintree



556
Spotted Gum



571
Sherbrooke



721
Cumberland



730
Boston



790
Midnight

Apollo 1500



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Manufacturing Standards:

All specifications and colours are subject to manufacturing tolerances and may be changed or discontinued without notice. Product images are for reference only; actual colours may vary from samples due to printing variations, batch differences, and lighting conditions. All variations are within industry standards.

Natural Product Characteristics:

Hard flooring products may display natural variations in colour, grain, texture, and pattern between batches and individual planks or tiles. These variations are inherent characteristics of the product and do not constitute a manufacturing defect.

Water Resistant/Waterproof Flooring:

Water resistance and waterproof performance are subject to proper installation, ongoing maintenance, and compliance with local building codes and regulatory requirements.

Installation:

All hard flooring must be installed by a qualified professional in accordance with NZS AS 1884:2013, relevant referenced standards for moisture testing and subfloor preparation (e.g. AS/NZS 1080 where applicable), recognised industry best practice, and the applicable Godfrey Hirst installation instructions. Proper subfloor preparation, moisture management, and acclimatisation are essential to ensure product performance and longevity.

Maintenance:

Maintenance requirements vary by product type. Refer to the specific care and maintenance guidelines for your flooring product to ensure optimal performance and longevity.

Product-Specific Notes:

Timber: Nested/random lengths may occur. As this is a natural product, some boxes may include one 'nested' board (i.e. two boards comprising the quoted board length). All boxes will provide the coverage quoted.

Vinyl Sheet: Each colour has a specific pattern repeat and laying direction—refer to the Product Specification Sheet for details. Pay particular attention to the directional arrow to determine if the design should be installed in a standard or reverse direction. LRV indicates Light Reflectance Value, PR is Pattern Repeat, and PTS denotes Plank/Tile Size.

Warranty:

All Godfrey Hirst floors carry a comprehensive warranty supported by New Zealand after-sales service. As a New Zealand manufacturer, we recognise all consumer rights under the Consumer Guarantees Act 1993 and match any equivalent performance guarantee offered in the marketplace at the time of purchase. Commercial warranties are issued project-by-project with specific terms and conditions.

For detailed warranty information, installation guidelines, care instructions, and product characteristics, visit www.godfreyhirst.com or call 0800 500 210. For commercial project-specific warranty enquiries, contact your GH Commercial Account Manager. Test results and certificates available on request.