

TECHNICAL SPECIFICATIONS

Country of Origin:	China	Colours:	12 Standard
Total Product Thickness:	6.5mm	Backing:	1.5mm Acoustic Backing
Hard Flooring Size:	152mm x 1830mm	Installation Method:	Unipush® -tap fold-down
Type:	Hybrid Flooring	Wear Layer:	0.5mm
Units Per Box:	6 boards	m ² per box:	1.67
m ² per pallet:	110.22	Finish:	Matte
Surface:	Embossed	Profile:	Micro Bevel
Substrate Layer:	Trigon® Core Technology (Limestone Composite)	Top Layer:	Decorative Film & Wear Layer
Protective Coating:	PUR	Quickship AU:	Blackbutt Ivory, Blackbutt Limed, Spotted Gum Blonde, Blackbutt Sandbank, Spotted Gum Coastal, Blackbutt Elegant, Spotted Gum Riverbank, Blackbutt Classic, Spotted Gum Natural, Spotted Gum Ash
Quickship QLD:	Blackbutt Ivory, Spotted Gum Blonde, Spotted Gum Coastal, Spotted Gum Riverbank, Blackbutt Classic, Blackbutt Stormy	Quickship WA:	Blackbutt Ivory, Blackbutt Limed, Spotted Gum Blonde, Blackbutt Sandbank, Spotted Gum Coastal, Blackbutt Elegant, Spotted Gum Riverbank, Blackbutt Classic, Spotted Gum Natural, Spotted Gum Ash, Blackbutt Stormy, Spotted Gum Burnt

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 10.9kW/m ²
Colourfast to light:	(EN ISO 105-B02) Grade 6
Light Reflectance:	Available on Request
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 81% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: -0.00%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Global GreenTag, GreenRate Level A certified
Green Star:	Environmental Certification Scheme (ECS). Level 2 achieving 12+ Points meeting Best Practice Requirements. Certificate #ECSR06
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Apollo Hardwood



Micro Bevel Edge



Matte Finish



Mid Range



Global GreenTag
GreenRate Level A



ISO 9001 Quality
Management System



ISO 14001 Environment
Management System



0.5mm Wear Layer



Trigon Core Technology



ECS Level 2



Celebrating Australian
Species



Waterproof Surface



Waterproof Core



Codemark Certified for
Apollo Hybrid Flooring



Codemark Certified
Waterproof


Apollo Hardwood




105
Blackbutt Ivory




505
Blackbutt Limed




520
Spotted Gum Blonde




525
Blackbutt Sandbank




530
Spotted Gum Coastal




535
Blackbutt Elegant




540
Spotted Gum
Riverbank



545
Blackbutt Classic



555
Spotted Gum Natural



710
Spotted Gum Ash



735
Blackbutt Stormy



790
Spotted Gum Burnt

Apollo Hardwood



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.