Apollo Hardwood

TECHNICAL SPECIFICATIONS

Country of Origin:	China
Total Product Thickness:	6.5mm
Hard Flooring Size:	152mm x 1830mm
Type:	Hybrid Flooring
Units Per Box:	6 boards
m^2 per pallet:	110.22
Surface:	Embossed
Substrate Layer:	Trigon® Core Technology (Limestone Composite)
Protective Coating:	PUR
Quickship QLD:	Blackbutt Classic, Spotted Gum Riverbank, Spotted Gum Coastal, Spotted Gum Blonde, Blackbutt Ivory

Colours:	10 Standard
Backing:	1.5mm Acoustic Backing
Installation Method:	Unipush® -tap fold-down
Wear Layer:	0.5mm
m^2 per box:	1.67
Finish:	Matte
Profile:	Micro Bevel
Top Layer:	Decorative Film & Wear Layer
Quickship AU:	Spotted Gum Ash, Spotted Gum Natural, Blackbutt Classic, Spotted Gum Riverbank, Blackbutt Elegant, Spotted Gum Coastal, Blackbutt Sandbank, Spotted Gum Blonde, Blackbutt Limed, Blackbutt Ivory
Quickship WA:	Spotted Gum Ash, Spotted Gum Natural, Blackbutt Classic, Spotted Gum Riverbank, Blackbutt Elegant, Spotted Gum Coastal, Blackbutt Sandbank, Spotted Gum Blonde, Blackbutt Limed, Blackbutt Ivory

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 10.9kW/m2
Colourfast to light:	(EN ISO 105-B02) Grade 6
Light Reflectance:	Available on Request
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 81% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: -0.00%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Green Star:	Environmental Certification Scheme (ECS). Level 2 achieving 12+ Points meeting Best Practice Requirements. Certificate #ECSR06
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Apollo Hardwood

COMMERCIAL



Micro Bevel Edge



Matte Finish



Mid Range



ISO 9001 Quality Management System



ISO 14001 Environment Management System



0.5mm Wear Layer



Trigon Core Technology



ECS Level 2



Celebrating Australian Species



Waterproof Surface



Waterproof Core



Codemark Certified for Apollo Hybrid Flooring



Codemark Certified Waterproof


Apollo Hardwood



105
Blackbutt Ivory




505
Blackbutt Limed




520
Spotted Gum Blonde




525
Blackbutt Sandbank



530
Spotted Gum Coastal




535
Blackbutt Elegant




540
Spotted Gum Riverbank



545
Blackbutt Classic



555
Spotted Gum Natural



710
Spotted Gum Ash

General Enquiries: 1300 300 821
ghcommercial.com

Apollo Hardwood

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.