

# Apollo Select Oak



## TECHNICAL SPECIFICATIONS

Colours:	6 Standard	Total Product Thickness:	6.5mm
Backing:	1.5mm Acoustic Backing	Hard Flooring Size:	203mm x 1524mm
Installation Method:	Uniclic®	Type:	Hybrid Flooring
Wear Layer:	0.5mm	Units Per Box:	6
m <sup>2</sup> per box:	1.847	m <sup>2</sup> per pallet:	103.43
Finish:	Matte	Surface:	Embossed in Register
Profile:	Micro Bevel	Substrate Layer:	Trigon® Core Technology (Limestone Composite)
Top Layer:	Decorative Film & Wear Layer	Protective Coating:	PUR & Scratch Resistance
Quickship QLD:	Natural Oak, Blonde Oak, Nordic Oak, Smoked Oak, Platinum Oak, Cinder Oak		

## PERFORMANCE

Flammability:	(EN ISO 9239) CRF 10.9kW/m <sup>2</sup>
Colourfast to light:	(ISO 105-B02) Grade 6
Light Reflectance:	Available on Request
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 81% minutes
Dimensional Stability:	(ISO 23999) Length: 0.0, Width: 0.0, Curling: 0.0
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3

## SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Global GreenTag, GreenRate Level A certified
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Global GreenTag  
GreenRate Level A



Green Building Council



ISO 9001 Quality  
Management System



ISO 14001 Environment  
Management System



Micro Bevel Edge



Matte Finish



0.5mm Wear Layer



Premium




# Apollo Select Oak




# Apollo Select Oak




300  
Natural Oak



500  
Blonde Oak




530  
Nordic Oak



580  
Smoked Oak



700  
Platinum Oak



790  
Cinder Oak

# Apollo Select Oak



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.

\*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.