Apollo Select Oak

TECHNICAL SPECIFICATIONS

Colours:	6 Standard
Backing:	1.5mm Acoustic Backing
Installation Method:	Uniclic®
Wear Layer:	0.5mm
m² per box:	1.847
Finish:	Matte
Profile:	Micro Bevel
Top Layer:	Decorative Film & Wear Layer
Quickship QLD:	Cinder Oak, Platinum Oak, Smoked Oak, Nordic Oak, Blonde Oak, Natural Oak

Total Product Thickness:	6.5mm
Hard Flooring Size:	203mm x 1524mm
Type:	Hybrid Flooring
Units Per Box:	6
m² per pallet:	103.43
Surface:	Embossed in Register
Substrate Layer:	Trigon® Core Technology (Limestone Composite)
Protective Coating:	PUR & Scratch Resistance

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 10.9kW/m2
Colourfast to light:	(ISO 105-B02) Grade 6
Light Reflectance:	Available on Request
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 81% minutes
Dimensional Stability:	(ISO 23999) Length: 0.0, Width: 0.0, Curling: 0.0
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Green Building Council

ISO 9001 Quality Management System

ISO 14001 Environment Management System

Micro Bevel Edge

Matte Finish

0.5mm Wear Layer

Premium

Apollo Select Oak




300
Natural Oak



500
Blonde Oak



530
Nordic Oak



580
Smoked Oak



700
Platinum Oak



790
Cinder Oak

General Enquiries: 1300 300 821
ghcommercial.com

Apollo Select Oak

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.