

TECHNICAL SPECIFICATIONS

Country of Origin:	China	Colours:	12 Standard
Total Product Thickness:	5.8mm	Backing:	1.5mm Acoustic Backing
Hard Flooring Size:	180mm x 1220mm	Installation Method:	Unipush®
Type:	Hybrid Flooring	Wear Layer:	0.3mm
Units Per Box:	10 boards	m ² per box:	2.196
m ² per pallet:	131.76	Finish:	Matte
Surface:	Embossed	Profile:	Micro Bevel
Substrate Layer:	Trigon® Core Technology (Limestone Composite)	Top Layer:	Decorative Film & Wear Layer
Protective Coating:	UV Coating	Quickship AU:	Shield, Python, Sunlight, Bronze, Wreath, New Eng Blackbutt, Grafton Spot.Gum, Western Blackbutt, Oracle, Dolphin
Quickship QLD:	Shield, Python, Sunlight, Wreath, New Eng Blackbutt, Grafton Spot.Gum, Western Blackbutt, Oracle		

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 10.6kW/m ²
Colourfast to light:	(EN ISO 105-B02) Grade 6
Light Reflectance:	Available on Request
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 92% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: -0.05%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Green Star:	Environmental Certification Scheme (ECS). Level 2 achieving 12+ Points meeting Best Practice Requirements. Certificate #ECSR05
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Micro Bevel Edge



Matte Finish



Mid Range



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Trigon Core Technology

Apollo



ECS Level 2



Celebrating Australian Species



Waterproof Surface



Waterproof Core




Codemark Certified for Apollo Hybrid Flooring




Codemark Certified Waterproof


Apollo



120
Shield



180
Python



320
Sunlight




510
Enlighten




515
Bronze




530
Wreath



545
New Eng Blackbutt




555
Grafton Spot.Gum



570
Western Blackbutt



625
Tallowood



710
Oracle



730
Dolphin

Apollo



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.