

Aquila Stone



TECHNICAL SPECIFICATIONS

Colours:	8 Standard	Total Product Thickness:	4.5mm
Hard Flooring Size:	304.8mm x 609.6mm	Installation Method:	Direct Stick
Notes:	^ Subject to proper installation and maintenance. Not suitable for areas with floor drains or excessive moisture/flooding.	Type:	Vinyl Plank Flooring
Wear Layer:	0.55mm	Units Per Box:	12
m ² per box:	2.23	m ² per pallet:	120.42
Finish:	Matte	Surface:	Embossed
Profile:	Square Edge or Grout Effect Edge. Refer to individual sku's.	Protective Coating:	Scratch & Slip Resistant
Quickship AU:	Pepper Sand, Tuscan Grout, Marble Ash, Sable Grout, Limestone Grout, Riverbed, Pebble Grey, Shale Grey		

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 8.6kW/m ² (with underlay): (EN ISO 9239) CRF 9.3kW/m ² (without underlay)
Colourfast to light:	(EN ISO 105-B02) 6-7
Light Reflectance:	505 Pepper Sand - 39.38% 760 Riverbed - 28.07% 710 Sable Grout - 40.64% 700 Marble Ash - 41.42% 765 Pebble Grey - 29.16% 750 Limed Blackbutt 30.11% 790 Shale Grey - 25.81% 540 Tuscan Grout - 38.41%
Contract Guarantee:	Available on request*
Classification:	(EN ISO 10874) Residential 23, Commercial 33
Smoke Value:	Direct Stick: (EN ISO 9239) 217% minutes (With Underlay): (EN ISO 9239) 144% minutes (without underlay)
Dimensional Stability:	(ISO 23999) Length: ≤0.05%, Width: ≤0.05%, Curling: ≤0.05%
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Best Environmental Practice PVC certified product, Global GreenTag, GreenRate Level A certified
Green Star:	Environmental Certification Scheme (ECS). Level 2+ achieving 12+ Points meeting Best Practice Requirements. Certificate #ECSR05
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Aquila Stone



Matte Finish



0.55mm Wear Layer



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Green Building Council



ECS Level 2+




Best Environmental Practice PVC




Global GreenTag GreenRate Level A


Aquila Stone




505
Pepper Sand



540
Tuscan Grout




700
Marble Ash




710
Sable Grout




750
Limestone Grout



760
Riverbed



765
Pebble Grey



790
Shale Grey

Aquila Stone



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst vinyl plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.