

# Aquila Wood



## TECHNICAL SPECIFICATIONS

Country of Origin:	South Korea	Colours:	12 Standard
Total Product Thickness:	4.5mm	Hard Flooring Size:	235mm x 1505mm
Installation Method:	Direct Stick	Notes:	^ Subject to proper installation and maintenance. Not suitable for areas with floor drains or excessive moisture/flooding.
Type:	Vinyl Plank Flooring	Wear Layer:	0.55mm
Units Per Box:	6	m <sup>2</sup> per box:	2.12
m <sup>2</sup> per pallet:	144.16	Finish:	Matte
Surface:	Embossed	Profile:	Micro Bevel
Protective Coating:	Scratch & Slip Resistant	Quickship AU:	Woodrow, Flora, Hazel, Faye, Teak, Limed Blackbutt, Coastal Spotted Gum, Blonde Spotted Gum, Milton, Orion

## PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 8.6kW/m <sup>2</sup>   With Underlay: (EN ISO 9239) CRF 9.3kW/m <sup>2</sup>
Colourfast to light:	(EN ISO 105-B02) 6-7
Light Reflectance:	190 Woodrow - 10.89%   300 Irving - 32.54%   350 Flora - 27.66%   500 Hazel - 26.92%   510 Faye - 24.85%   520 Teak - 17.12%   525 Limed Blackbutt - 24.95%   535 Coastal Spotted Gum - 14.81%   545 Classic Blackbutt - 16.85%   555 Blonde Spotted Gum - 21.04%   720 Milton - 36.76%   780 Orion - 25.38%
Contract Guarantee:	Available on request*
Classification:	(EN ISO 10874) Residential 23, Commercial 33
Smoke Value:	Direct Stick: (EN ISO 9239) 217% minutes   With Underlay: (EN ISO 9239) 144% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: 0.05%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide <a href="http://www.ghcommercial.com">www.ghcommercial.com</a>

## SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Best Environmental Practice PVC certified product, Global GreenTag, GreenRate Level A certified
Green Star:	Environmental Certification Scheme (ECS). Level 2+ achieving 12+ Points meeting Best Practice Requirements. Certificate #ECSR05
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

# Aquila Wood



Micro Bevel Edge



Matte Finish



0.55mm Wear Layer



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Green Building Council



Best Environmental Practice PVC



ECS Level 2+



Global GreenTag GreenRate Level A



Celebrating Australian Species



Waterproof Surface




Waterproof Core



Waterproof


# Aquila Wood




190  
Woodrow



300  
Irving




350  
Flora




500  
Hazel




510  
Faye



520  
Teak




525  
Limed Blackbutt



535  
Coastal Spotted Gum




545  
Classic Blackbutt



555  
Blonde Spotted Gum



720  
Milton



780  
Orion

# Aquila Wood



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst vinyl plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.

\*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.