Aquila Wood

TECHNICAL SPECIFICATIONS

Country of Origin:	South Korea
Total Product Thickness:	4.5mm
Installation Method:	Direct Stick
Type:	Vinyl Plank Flooring
Units Per Box:	6
m^2 per pallet:	144.16
Surface:	Embossed
Protective Coating:	Scratch & Slip Resistant

Colours:	12 Standard
Hard Flooring Size:	235mm x 1505mm
Notes:	^Subject to proper installation and maintenance. Not suitable for areas with floor drains or excessive moisture/ flooding.
Wear Layer:	0.55mm
m^2 per box:	2.12
Finish:	Matte
Profile:	Micro Bevel
Quickship AU:	Orion, Milton, Blonde Spotted Gum, Coastal Spotted Gum, Limed Blackbutt, Teak, Faye, Hazel, Flora, Woodrow

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 8.6kW/m2 | With Underlay: (EN ISO 9239) CRF 9.3kW/m2
Colourfast to light:	(EN ISO 105-B02) 6-7
Light Reflectance:	190 Woodrow - 10.89% | 300 Irving - 32.54% | 350 Flora - 27.66% | 500 Hazel - 26.92% | 510 Faye - 24.85% | 520 Teak - 17.12% | 525 Limed Blackbutt - 24.95% | 535 Coastal Spotted Gum - 14.81% | 545 Classic Blackbutt - 16.85% | 555 Blonde Spotted Gum - 21.04% | 720 Milton - 36.76% | 780 Orion - 25.38%
Contract Guarantee:	Available on request*
Classification:	(EN ISO 10874) Residential 23, Commercial 33
Smoke Value:	Direct Stick: (EN ISO 9239) 217% minutes | With Underlay: (EN ISO 9239) 144% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: 0.05%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Best Environmental Practice PVC certified product
Green Star:	Environmental Certification Scheme (ECS). Level 2+ achieving 12+ Points meeting Best Practice Requirements. Certificate #ECSR05
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Aquila Wood

Micro Bevel Edge

Matte Finish

0.55mm Wear Layer

ISO 9001 Quality Management System

ISO 14001 Environment Management System

Green Building Council

Best Environmental Practice PVC

ECS Level 2+


Celebrating Australian Species

Waterproof Surface

Waterproof Core

Waterproof

Aquila Wood




190
Woodrow



300
Irving




350
Flora




500
Hazel




510
Faye



520
Teak




525
Limed Blackbutt



535
Coastal Spotted Gum



545
Classic Blackbutt



555
Blonde Spotted Gum



720
Milton



780
Orion

General Enquiries: 1300 300 821
ghcommercial.com

Aquila Wood

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst vinyl plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.