

Concourse II



TECHNICAL SPECIFICATIONS

Country of Origin:	Australia	Colours:	7 Standard
Yarn:	100% Statron Plus® Solution Dyed Nylon	Surface Texture:	Textured Loop Pile
Gauge:	47.2/10cm (1/12th Gauge)	Total Product Thickness:	7 (+/- 1.0)mm
Pile Height:	4.5 (+/- 1.0)mm	Pile Weight:	745.00g/m ² (22oz)
Backing:	Action Bac®	Installation Method:	Direct Stick
Type:	Commercial Broadloom	Roll Width:	4.00
Pattern Repeat:	51cm (w) x 122cm (l)	Quickship AU:	Loam, Soldier, Monolith, Gypsum, Thunder

PERFORMANCE

Anti-Static:	(AATCC 134) $\leq 3.5KV$ at 21°C & 20% Relative Humidity
Flammability:	CRF 7.9kW/m ² (Direct Stick)~
Stain Resistance:	Stain Warden®
Biocontaminant Control:	Bioshield® Antimicrobial Control
ACCS Rating:	Contract Extra Heavy Duty - 4 Star, Residential Extra Heavy Duty & Stairs - 6 Star
Smoke Value:	48% minutes (Direct Stick)
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS). Level 4+. Achieves 12+ Points meeting Best Practice Requirements - Certificate #21161
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.



Australian Made



PVC Free



Contract Extra Heavy Duty - 4 Star



Residential Extra Heavy Duty & Stairs - 6 Star



ECS Level 4



Green Building Council



ISO 9001 Quality Management System



ISO 14001 Environment Management System




AS 4801



Statron Plus® SDN



Declare



Affordable

Concourse II




Declare® Red List Free




Textured Loop Pile


Concourse II




710
Overcast



735
Loam



750
Soldier



760
Monolith



775
Gypsum



795
Thunder



875
Cosmos

Concourse II



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpets must be installed in accordance with the latest AS2455 and any relevant GH Commercial Carpet Installation Instructions. Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling. ~Test results and certificates are available on request.

*This warranty is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.