Corsica Chevron

TECHNICAL SPECIFICATIONS

Colours:	4 Standard
Backing:	Ply
Installation Method:	Tongue & Groove
Wear Layer:	3mm
m² per box:	1.55
Finish:	Matte Finish with light brush
Profile:	Micro Bevel Edge
Protective Coating:	UV Cured Lacquer

Total Product Thickness:	14mm
Hard Flooring Size:	125mm x 620mm
Type:	Timber Flooring
Units Per Box:	20 boards (10 left, 10 right)
m² per pallet:	74.4
Surface:	French Oak Veneer
Substrate Layer:	Multiply
Quickship AU:	Weathered Oak, Coastal Oak, Natural Oak Brush, Coffee Oak

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 3.8kW/m2
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 17% minutes
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P4
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Moisture Content:	(EN 131831-1) 8-11% (+/-2%) at time of delivery
Lipping:	(EN13489) ≤0.2mm

SUSTAINABILITY

Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparency:	PEFC Chain of Custody certified.
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Real Timber Surface

Natural Variation

Micro Bevel Edge

PEFC CoC Certified

Green Building Council

ISO 9001 Quality Management System

ISO 14001 Environment Management System

Premium

General Enquiries: 1300 300 821
ghcommercial.com


Corsica Chevron



180
Coffee Oak



310
Natural Oak Brush



510
Coastal Oak



560
Weathered Oak

General Enquiries: 1300 300 821
ghcommercial.com

Corsica Chevron

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst engineered timber floors must be installed in accordance with the relevant Australian Standards and in conjunction with the Godfrey Hirst Timber Floors Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

Note: Nested/Random lengths may occur. As this is a natural products, some boxes may include one 'nested' board (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.