

# Corsica Herringbone



## TECHNICAL SPECIFICATIONS

Colours:	4 Standard	Total Product Thickness:	14mm
Backing:	Ply	Hard Flooring Size:	125mm x 600mm
Installation Method:	Tongue & Groove	Type:	Timber Flooring
Wear Layer:	3mm	Units Per Box:	20 boards (10 left, 10 right)
m <sup>2</sup> per box:	1.5	m <sup>2</sup> per pallet:	72
Finish:	Matte Finish with light brush	Surface:	French Oak Veneer
Profile:	Micro Bevel Edge	Substrate Layer:	Multiply
Protective Coating:	UV Cured Lacquer	Quickship AU:	Coffee Oak, Natural Oak Brush, Coastal Oak, Weathered Oak

## PERFORMANCE

Flammability:	(EN ISO 9239) CRF 3.8kW/m <sup>2</sup>
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 17% minutes
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P4
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide <a href="http://www.ghcommercial.com">www.ghcommercial.com</a>
Moisture Content:	(EN 131831-1) 8-11% (+/-2%) at time of delivery
Lipping:	(EN13489) ≤0.2mm

## SUSTAINABILITY

Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparency:	PEFC Chain of Custody certified.
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Real Timber Surface



Natural Variation



Micro Bevel Edge



PEFC CoC Certified



Green Building Council



ISO 9001 Quality Management System



ISO 14001 Environment Management System




Premium


# Corsica Herringbone




180  
Coffee Oak



310  
Natural Oak Brush



510  
Coastal Oak



560  
Weathered Oak

# Corsica Herringbone



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst engineered timber floors must be installed in accordance with the relevant Australian Standards and in conjunction with the Godfrey Hirst Timber Floors Installation Instructions.

\*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

Note: Nested/Random lengths may occur. As this is a natural products, some boxes may include one 'nested' board (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.