Distressed Plaid

TECHNICAL SPECIFICATIONS

Country of Origin:	Australia
Yarn:	100% Nylon
Gauge:	47.2/10cm (1/12th Gauge)
Pile Height:	6.5 (+/- 1.0)mm
Backing:	Action Bac®
Type:	Commercial Broadloom
Pattern Repeat:	1.96m (W) x 3.92m (L)
Colours:	4 Standard
Surface Texture:	Patterned Textured Loop Pile
Total Product Thickness:	9 (+/- 1.0)mm
Pile Weight:	745.00 g/m² (22 oz)
Installation Method:	Direct Stick Recommended
Roll Width:	1.96m

PERFORMANCE

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for flooring in Class 2-9 buildings~
Colourfast to light:	(ISO 105-B-02-1994) 5-6
Light Reflectance:	Available on Request
Stain Resistance:	Stain Warden®
Biocontaminant Control:	Bioshield® Antimicrobial Control
ACCS Rating:	Contract Extra Heavy Duty - 4 Star
Contract Guarantee:	10 Years available on request*
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS). Level 4 - Certificate
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.

AVAILABILITY

Backing Options:	Quick Comfort® cushion backing

Australian Made

Designer Jet Sheet on Action Bac

PVC Free

BPA Free

Pthalate Free

Contract Extra Heavy Duty - 4 Star

Distressed Plaid

ECS Level 4

Green Building Council

ISO 9001 Quality Management System

ISO 14001 Environment Management System

AS 4801

Designer Jet

Patterned Cut Pile

Mid Range

Declare® Red List Free

Distressed Plaid



2021 1034



2021 1033



2021 1032



2021 103

Distressed Plaid

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpets must be installed in accordance with the latest AS2455 and any relevant GH Commercial Carpet Installation Instructions.
Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear.
Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.
~Test results and certificates are available on request.
*This warranty is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.