

Erosion of Time



TECHNICAL SPECIFICATIONS

Country of Origin:	Australia	Colours:	6 Standard
Yarn:	100% Nylon	Surface Texture:	Patterned Cut Pile
Gauge:	39.4/10cm (1/10th Gauge)	Total Product Thickness:	8.5 (+/- 1.0)mm
Pile Height:	6 (+/- 1.0)mm	Pile Weight:	1187g/m ² (35oz)
Backing:	Enviro Bac®	Size:	250mm x 1000mm
Installation Method:	Herringbone, Ashlar, Brick	Type:	Carpet Tiles and Planks
Units Per Box:	14	m ² per box:	3.5
m ² per pallet:	126		

PERFORMANCE

Anti-Static:	(AATCC 134) $\leq 3.5KV$ at 21°C & 20% Relative Humidity
Flammability:	Meets the requirements of the NCC Spec. C1.10 relating to fire hazard properties for flooring in class 2-9 buildings (including health and aged care buildings). Meets the requirements of the New Zealand Buildings Code Section C3 - Fire Affecting Areas Beyond the Fire Source.
Colourfast to light:	(ISO 105-B-02-1994) 5-6
Light Reflectance:	Available on Request
Stain Resistance:	Stain Warden®
Biocontaminant Control:	Bioshield® Antimicrobial Control
ACCS Rating:	Contract Extra Heavy Duty - 4 Star
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS). Level 4+. Achieves 12+ Points meeting Best Practice Requirements - Certificate #25239
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.

AVAILABILITY

Backing Options:	Enviro Bac Lite® cushion backing, Enviro Bac Plus® cushion backing
------------------	--

Erosion of Time



Australian Made

Declare.

Designer Jet Carpet Tiles & Planks on Enviro Bac and Enviro Bac Plus



ISO 9001 Quality Management System



ISO 45001 OHS Management System



ISO 14001 Environment Management System

Designer Jet®

Designer Jet



Declare® Red List Free



Green Building Council



Contract Extra Heavy Duty - 4 Star



ECS Level 4+

Erosion of Time



5100
Weathered Mesh



5800
Harmonic Pipes



7100
Ancient Hollow



7500
Shore Break



8200
Triform



9100
Erosand

Erosion of Time



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions. Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling. ~Test results and certificates are available on request.

*Guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.