Ironbark

TECHNICAL SPECIFICATIONS

Collection:	Native
Colours:	5 Standard
Surface Texture:	Patterned Textured Loop Pile
Total Product Thickness:	6.5 (+/- 1.0)mm
Pile Weight:	745.00 g/m² (22 oz)
Carpet Tiles & Planks Size:	250mm x 1000mm
Type:	Carpet Tiles and Planks
m² per box:	4
Pattern Repeat:	Not Applicable

Country of Origin:	Australia
Yarn:	100% Statron Plus® Solution Dyed Nylon
Gauge:	47.2/10cm (1/12th Gauge)
Pile Height:	4 (+/- 1.0)mm
Backing:	Enviro Bac®
Installation Method:	Herringbone, Ashlar, Brick
Units Per Box:	16
m² per pallet:	144
Quickship AU:	Granite, Serpentine, Yarraman, Hill Grey

PERFORMANCE

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for flooring in Class 2-9 buildings (including health and aged care)~
Colourfast to light:	(ISO 105-B-02-1994) 6-7
Light Reflectance:	Available on Request
Stain Resistance:	Stain Warden®
Biocontaminant Control:	Bioshield® Antimicrobial Control
ACCS Rating:	Contract Extra Heavy Duty - 4 Star
Contract Warranty:	15 Years Available on Request*
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Environmental Product Declaration:	Environmental Product Declaration in accordance with ISO 14025 and EN 15804+A2
Green Star:	Environmental Certification Scheme (ECS). Level 4+. Achieves 12+ Points meeting Best Practice Requirements - Certificate #22250
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.

AVAILABILITY

Size Options:	250mm x 1000mm carpet plank, 500mm x 500mm carpet tile
Backing Options:	Enviro Bac Plus® cushion backing

Ironbark

Australian Made

ISO 14001 Environment Management System

ISO 9001 Quality Management System

Contract Extra Heavy Duty - 4 Star

PVC Free

Green Building Council

SDN Carpet Tiles and Planks on Enviro Bac and Enviro Bac Plus

Statron Plus® SDN

Patterned Textured Loop Pile

Declare® Red List Free

Premium


ECS Level 4+

SDN Carpet Tiles with Enviro Bac®

Ironbark




91
Hill Grey



93
Yarraman



95
Wandi



97
Serpentine



98
Granite

Ironbark

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.
Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear.
Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.
~Test results and certificates are available on request.
*Guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.