Isafe 70

TECHNICAL SPECIFICATIONS

Country of Origin:	Belgium
Total Product Thickness:	2.15mm
Notes:	Matching Heat Welds Available. See documents tab for more information.
Wear Layer:	0.7mm
Surface:	Embossed
Roll Width:	Width: 2m, Length: 20m

Colours:	6 Standard
Installation Method:	Direct Stick
Type:	Vinyl Sheet Flooring
Finish:	Matte
Protective Coating:	HyperGrip+ Performance Barrier
Seaming Method:	Matching Heat Welds Available

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 7.4 kW/m2
Contract Guarantee:	Available on request*
Smoke Value:	Direct Stick: (EN ISO 9239) 146% minutes
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	P4
Recommended Adhesive:	See Adhesive Recommendations Flyer in the Documents tab above.

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Heterogenous Vinyl Sheet



2m Wide



HyperGrip+



Sanitec


Water Resistant



Affordable



Direct Stick




ISO 9001 Quality Management System



ISO 14001 Environment Management System

Isafe 70




523
Light Green




531
Sand



577
Steel Blue



594
Gainsboro Grey



597
Dim Grey



599
Ink

Isafe 70

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial vinyl sheet products must be installed in accordance with relevant Australian Standards and in conjunction with the GH Commercial Vinyl Sheet Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.