

Legacy 1200



TECHNICAL SPECIFICATIONS

Colours:	12 Standard	Total Product Thickness:	8mm
Backing:	Balancing Layer	Size:	197mm x 1216mm
Installation Method:	Uniclic®	Type:	Laminate Flooring
Units Per Box:	9 boards	m ² per box:	2.16
m ² per pallet:	140.14	Finish:	Matte
Surface:	Embossed	Profile:	4 Sided Bevel
Substrate Layer:	860kg/m ³ High Density Fibreboard	Quickship AU:	Rustic Bronze, Amber Glow, Sunset Birch, Coastal Driftwood, Eastern Blackbutt, Evening Haze, Mocha Java, Pebble Bay, Seaside Oak, Ebony Ash

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 11kW/m ²
Smoke Value:	(EN ISO 9239) 4% minutes
Abrasion Rating:	(EN 13329) AC4
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS/NZ 4586-2013) P3

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Green Building Council



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Matte Finish



Mid Range



Celebrating Australian Species



Waterproof Surface




Water Resistant

Legacy 1200




170
Rustic Bronze



320
Amber Glow



510
Harbour Oak



520
Sunset Birch




525
Alpine Blackbutt




530
Coastal Driftwood



545
Eastern Blackbutt



550
Evening Haze



560
Mocha Java



700
Pebble Bay



730
Seaside Oak



790
Ebony Ash

Legacy 1200



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst laminate products must be installed in accordance with the relevant Australian Standards and in conjunction with the Godfrey Hirst Laminate Installation Instructions.

*Terms and conditions apply to all commercial warranties - please contact your GH Commercial Account Manager.