

Metropol Oak



TECHNICAL SPECIFICATIONS

Colours:	12 Standard	Total Product Thickness:	6.5mm
Backing:	1.5mm Acoustic Backing	Size:	182mm x 1830mm
Installation Method:	Uniclic®	Type:	Hybrid Flooring
Wear Layer:	0.5mm	Units Per Box:	4 boards
m ² per box:	1.332	m ² per pallet:	113.24
Finish:	Matte	Surface:	Embossed in Register
Profile:	Micro Bevel	Substrate Layer:	Trigon® Core Technology (Limestone Composite)
Top Layer:	Decorative Film & Wear Layer	Protective Coating:	Ceramic Bead
Quickship AU:	Mindil Oak, Anglesea Oak, Goolwa Oak, Bondi Oak, Flinders Oak, Seacliff Oak, Bruny Oak, Bells Oak, Burleigh Oak, Hyams Oak	Quickship QLD:	Bondi Oak
Quickship WA:	Mindil Oak, Whitehaven Oak, Anglesea Oak, Goolwa Oak, Bondi Oak, Flinders Oak, Seacliff Oak, Bruny Oak, Bells Oak, Burleigh Oak, Hyams Oak, Copalis Oak		

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 11.1kW/m ²
Colourfast to light:	(EN ISO 105-B02) ≥6
Light Reflectance:	100 - 55.8 110 - 43.5 170 - 12.3 180 - 8.1 300 - 18.2 500 - 33.6 510 - 27.6 520 - 24.9 540 - 26.5 720 - 30.2 730 - 13.1 790 - 15.3
Smoke Value:	(EN ISO 9239) 210% minutes
Dimensional Stability:	(ISO 23999) Length: 0.0, Width: 0.0, Curling: 0.0
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P4

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Micro Bevel Edge



Matte Finish



Mid Range



Codemark Certified For Metropol Hybrid Flooring



ISO 9001 Quality Management System



ISO 14001 Environment Management System

Metropol Oak



Trigon Core Technology



Celebrating Australian Species



Waterproof Surface



Waterproof Core




Codemark Certified Waterproof




ECS Level 2


Metropol Oak




100
Mindil Oak




110
Whitehaven Oak




170
Anglesea Oak




180
Goolwa Oak




300
Bondi Oak




500
Flinders Oak



510
Seacliff Oak



520
Bruny Oak



540
Bells Oak



720
Burleigh Oak



730
Hyams Oak



790
Copalis Oak

Metropol Oak



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.