

Modern Coastal



TECHNICAL SPECIFICATIONS

Colours:	3 Standard	Total Product Thickness:	14.2mm
Backing:	Ply	Hard Flooring Size:	135mm x 1820mm
Installation Method:	5G Insta Clic®	Type:	Timber Flooring
Wear Layer:	3.2mm	Units Per Box:	6 boards equivalent (32% Nested/Random lengths)
m ² per box:	1.474	m ² per pallet:	113.19
Finish:	Matte	Surface:	Australian Species Timber Veneer
Profile:	Micro Bevel Edge	Substrate Layer:	Hevea Core
Protective Coating:	UV Cured Lacquer	Quickship AU:	Tassie Oak, Blackbutt, Spotted Gum

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 5.1kW/m ²
Light Reflectance:	Available on request
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 11% minutes
Dimensional Stability:	-0.05 Length direction/Machine Direction, -0.10 Width Direction/Across Machine direction, 1.5mm Curling
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586 - 2013) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Moisture Content:	(EN 131831-1) 8-11% (+/-2%) at time of delivery

SUSTAINABILITY

Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Real Timber Surface



Natural Variation



Micro Bevel Edge



Premium



Matte Finish



ISO 9001 Quality Management System



ISO 14001 Environment Management System




Colour Toning




Celebrating Australian Species


Modern Coastal



515
Tassie Oak



545
Blackbutt



555
Spotted Gum

Modern Coastal



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst engineered timber floors must be installed in accordance with the relevant Australian Standards and in conjunction with the Godfrey Hirst Timber Floors Installation Instructions.

*This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.

□ Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Nested/Random lengths may occur. As this is a natural products, some boxes may include one 'nested' board (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.