Modularity

TECHNICAL SPECIFICATIONS

Country of Origin:	Australia
Yarn:	100% Solution Dyed Nylon
Gauge:	39.4/10cm (1/10th Gauge)
Pile Height:	7 (+/- 1.0)mm
Backing:	Enviro Bac Plus®
Installation Method:	Brick, Ashlar (Flexlok tabs recommended). Recommended installation: Half drop ashlar to disrupt join lines. Tiles laid with arrows facing viewer and where possible take into account any directional light.
Type:	Carpet Tiles and Planks
m^2 per box:	2.5
Pattern Repeat:	Not Applicable

Colours:	9 Standard
Surface Texture:	Cut Pile Twist
Total Product Thickness:	10.5 (+/- 1.0)mm
Pile Weight:	1120.00 g/m^2 (33 oz)
Carpet Tiles & Planks Size:	500mm x 500mm
Notes:	This is a modular product, dependent on lighting, colour choice, and other site conditions, joins may be visible and remain a natural feature of the product.
Units Per Box:	10
m^2 per pallet:	90

PERFORMANCE

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for flooring in Class 2-9 buildings (including health and aged care buildings)~
Light Reflectance:	Available on Request
Stain Resistance:	Stain Warden®
Biocontaminant Control:	Bioshield® Antimicrobial Control
ACCS Rating:	Contract Heavy Duty - 3 Star
Contract Guarantee:	15 Years Available on Request*
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free, Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS) Level 4 - Certificate #23337
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.

Declare

SDN Carpet Tiles and Planks on Enviro Bac and Enviro Bac Plus

ISO 9001 Quality Management System

ISO 14001 Environment Management System

ISO 45001 OHS Management System

Declare® Red List Free

Modularity

PVC Free

Australian Made

ECS Level 4

Cut Pile Twist

Mid Range

Contract Heavy Duty - 3 Star

Modularity



520
Serene




550
Panoramic



580
Luxe



585
Tranquil



740
Leisure



745
Elegance



750
Vogue



767
Modish



780
Scenic View

Modularity

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.
Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear.
Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.
~Test results and certificates are available on request.
*Guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.