

TECHNICAL SPECIFICATIONS

Colours:	12 Standard	Total Product Thickness:	2.5mm
Hard Flooring Size:	184mm x 1219mm	Installation Method:	Direct Stick
Notes:	^ Subject to proper installation and maintenance. Not suitable for areas with floor drains or excessive moisture/flooding.	Type:	Vinyl Plank Flooring
Wear Layer:	0.5mm	Units Per Box:	15
m ² per box:	3.37	m ² per pallet:	252.75
Finish:	Matte	Surface:	Embossed
Profile:	Micro Bevel	Protective Coating:	PUR + Scratch Resist + Stain Resist
Quickship QLD:	Pandora, Atlas, Iris, Artemis, Helios, Hades, Zephyr, Orion, Boreas, Aegean, Eos, Aether	Quickship WA:	Pandora, Atlas, Iris, Artemis, Helios, Hades, Zephyr, Orion, Boreas, Aegean, Eos, Aether

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 10.7kW/m ²
Colourfast to light:	(EN ISO 105-B02) ≥6
Light Reflectance:	170 - 11.53 190 - 7.62 510 - 21.19 520 - 27.72 525 - 28.69 530 - 21.12 535 - 21.86 560 - 19.35 565 - 24.53 570 - 28.90 580 - 34.27 720 - 33.62
Contract Warranty:	GH Commercial provides comprehensive warranties for our products. All warranties are issued on a project by project basis. Please contact us to discuss your requirements further.
Classification:	(EN ISO 10874) Residential 23, Commercial 33
Smoke Value:	Direct Stick: (EN ISO 9239) 53% minutes
Dimensional Stability:	(ISO 23999) Length: ≤0.05%, Width: ≤0.05%, Curling: ≤0.05%
Abrasion Rating:	(EN 660-2) Group T
Suitable for wet areas:	Yes - subject to proper installation and maintenance
Residual Indentation:	(ISO 24343-1) 0.03mm
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Green Star:	Environmental Certification Scheme (ECS). Level 2 achieving 12+ Points meeting Best Practice Requirements. Certificate #ECSR08
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Olympus Neo



Matte Finish



Micro Bevel Edge



ISO 9001 Quality Management System



ISO 14001 Environment Management System




ECS Level 2




0.55mm Wear Layer


Olympus Neo




170
Pandora



190
Atlas



510
Iris




520
Artemis




525
Helios




530
Hades



535
Zephyr



560
Orion




565
Boreas



570
Aegean



580
Eos



720
Aether

Olympus Neo



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.