

Olympus Stone



TECHNICAL SPECIFICATIONS

Colours:	8 Standard	Total Product Thickness:	2.5mm
Hard Flooring Size:	457mm x 457mm	Installation Method:	Direct Stick
Notes:	^ Subject to proper installation and maintenance. Not suitable for areas with floor drains or excessive moisture/flooding.	Type:	Vinyl Plank Flooring
Wear Layer:	0.5mm	Units Per Box:	16
m ² per box:	3.34	m ² per pallet:	160.32
Finish:	Matte	Surface:	Embossed
Profile:	Micro Bevel	Protective Coating:	Ceramic Bead
Quickship QLD:	Shoreline Terrazzo, Mineral Terrazzo, Arctic Grey, Mystic Grey, Stormy Ceppo, Iron Ceppo, Pewter Stone, Granite Stone	Quickship WA:	Shoreline Terrazzo, Mineral Terrazzo, Arctic Grey, Mystic Grey, Stormy Ceppo, Iron Ceppo, Pewter Stone, Granite Stone

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 10.7kW/m2
Colourfast to light:	(EN ISO 105-B02) ≥6
Light Reflectance:	105 - 59.01% 510 - 27.20% 705 - 53.58% 710 - 36.22% 720 - 33.89% 725 - 32.07 765 - 27.83% 790 - 12.11%
Contract Warranty:	GH Commercial provides comprehensive warranties for our products. All warranties are issued on a project by project basis. Please contact us to discuss your requirements further.
Classification:	(EN ISO 10874) Residential 23, Commercial 33
Smoke Value:	Direct Stick: (EN ISO 9239) 53% minutes
Dimensional Stability:	(ISO 23999) Length: ≤0.05%, Width: ≤0.05%, Curling: ≤0.05%
Abrasion Rating:	(EN 660-2) Group T
Suitable for wet areas:	Yes - subject to proper installation and maintenance
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Matte Finish



0.55mm Wear Layer



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Green Building Council




ECS Level 2


Olympus Stone




Olympus Stone




105
Shoreline Terrazzo




510
Mineral Terrazzo




705
Arctic Grey




710
Mystic Grey




720
Stormy Ceppo



725
Iron Ceppo



765
Pewter Stone



790
Granite Stone

Olympus Stone



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.