

Polaris 1200



TECHNICAL SPECIFICATIONS

Colours:	12 Standard	Total Product Thickness:	3mm
Size:	228mm x 1219mm	Installation Method:	Direct Stick
Type:	Vinyl Plank Flooring	Wear Layer:	0.5mm
Units Per Box:	12	m ² per box:	3.35
m ² per pallet:	187.6	Finish:	Matte
Surface:	Embossed	Profile:	Square Edge
Protective Coating:	PUR	Quickship AU:	Tan Hardwood, Bright Spotted Gum, Hazel Blackbutt, Brindle Spotted Gum, Silver Hardwood, Iron Spotted Gum
Quickship QLD:	Brindle Spotted Gum, Silver Hardwood		

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 10.0kW/m ² With Underlay: (EN ISO 9239) CRF 7.0kW/m ²
Colourfast to light:	(EN ISO 105-B02) 6-7
Light Reflectance:	110 - 31.89 300 - 20.07 510 - 28.06 525 - 20.60 545 - 13.37 555 - 13.70 560 - 18.15 570 - 9.60 585 - 8.64 710 29.61 735 - 14.38 790 - 10.41
Smoke Value:	Direct Stick: (EN ISO 9239) 132% minutes With Underlay: (EN ISO 9239) 184% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: 0.05%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P5
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Thermal Conductivity:	TBA

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Green Star:	Environmental Certification Scheme (ECS). Level 1 Certificate #ECSR04
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Matte Finish



Green Building Council



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Affordable



Colour Variation

Polaris 1200



0.5mm Wear Layer



Celebrating Australian Species



Waterproof Surface



Waterproof Core




Waterproof

Polaris 1200



110
Pearl Oak



300
Tan Hardwood



510
Flax Oak




525
Silk Spotted Gum



545
Classic Blackbutt




555
Bright Spotted Gum




560
Hazel Blackbutt



570
Tawny Blackbutt




585
Brindle Spotted Gum



710
Silver Hardwood



735
Stony Blackbutt



790
Iron Spotted Gum

Polaris 1200



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst vinyl plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.