Polaris 1200

TECHNICAL SPECIFICATIONS

Colours:	12 Standard
Hard Flooring Size:	228mm x 1219mm
Type:	Vinyl Plank Flooring
Units Per Box:	12
m^2 per pallet:	187.6
Surface:	Embossed
Protective Coating:	PUR
Quickship QLD:	Silver Hardwood, Brindle Spotted Gum

Total Product Thickness:	3mm
Installation Method:	Direct Stick
Wear Layer:	0.5mm
m^2 per box:	3.35
Finish:	Matte
Profile:	Square Edge
Quickship AU:	Iron Spotted Gum, Silver Hardwood, Brindle Spotted Gum, Hazel Blackbutt, Bright Spotted Gum, Tan Hardwood

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 10.0kW/m2 | With Underlay: (EN ISO 9239) CRF 7.0kW/m2
Colourfast to light:	(EN ISO 105-B02) 6-7
Light Reflectance:	110 - 31.89 | 300 - 20.07 | 510 - 28.06 | 525 - 20.60 | 545 - 13.37 | 555 - 13.70 | 560 - 18.15 | 570 - 9.60 | 585 - 8.64 | 710 29.61 | 735 - 14.38 | 790 - 10.41
Contract Guarantee:	Available on request*
Smoke Value:	Direct Stick: (EN ISO 9239) 132% minutes | With Underlay: (EN ISO 9239) 184% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: 0.05%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Thermal Conductivity:	TBA

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Green Star:	Environmental Certification Scheme (ECS). Level 1 Certificate #ECSR04
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Matte Finish

Green Building Council

ISO 9001 Quality Management System

ISO 14001 Environment Management System

Affordable

Colour Variation

General Enquiries: 1300 300 821
ghcommercial.com

Polaris 1200



0.5mm Wear Layer



Celebrating Australian Species



Waterproof Surface



Waterproof Core



Waterproof

General Enquiries: 1300 300 821
ghcommercial.com

Polaris 1200



110
Pearl Oak



300
Tan Hardwood




510
Flax Oak




525
Silk Spotted Gum



545
Classic Blackbutt




555
Bright Spotted Gum




560
Hazel Blackbutt



570
Tawny Blackbutt




585
Brindle Spotted Gum



710
Silver Hardwood



735
Stony Blackbutt



790
Iron Spotted Gum

General Enquiries: 1300 300 821
ghcommercial.com

Polaris 1200

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst vinyl plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.