

## TECHNICAL SPECIFICATIONS

Country of Origin:	Australia	Colours:	10 Standard
Yarn:	100% Solution Dyed Nylon	Surface Texture:	Cut Pile Twist
Gauge:	39.4/10cm (1/10th Gauge)	Total Product Thickness:	9.5 (+/- 1.0)mm
Pile Height:	7.5 (+/- 1.0)mm	Pile Weight:	950.00g/m <sup>2</sup> (28oz)
Backing:	EnduraBac®	Installation Method:	Direct Stick, Conventionally Laid
Type:	Residential Broadloom	Roll Width:	3.66
Pattern Repeat:	Not Applicable		

## PERFORMANCE

Anti-Static:	(AATCC 134) <math>\leq 3.5\text{KV}</math> at 21°C & 20% Relative Humidity
Flammability:	Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for flooring in Class 2-9 buildings (including health and aged care buildings)~
Colourfast to light:	(ISO 105-B-02-1994) 5-6
Light Reflectance:	Available on Request
Stain Resistance:	Stain Block®
ACCS Rating:	Contract Medium Duty - 2 Star
Contract Guarantee:	5 Year Contract Guarantee Available on Request*

## SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS). Level 4+. Achieves 12+ Points meeting Best Practice Requirements - Certificate #17003
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.



Australian Made



Declare® Red List Free



Contract Medium Duty - 2 Star



Cut Pile Twist



Green Building Council



ISO 9001 Quality Management System



ISO 14001 Environment Management System



ISO 45001 OHS Management System



Declare




Affordable



ECS Level 4+

# Prelude




185  
Cocoa



195  
Aniseed



505  
Balsa Stone




510  
Sandblast




550  
Nutmeg




715  
Penny



730  
Quarter



740  
Ashwood



760  
Monogrey



780  
Peppercorn

# Prelude



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpets must be installed in accordance with the latest AS2455 and any relevant GH Commercial Installation Instructions. ~Test results and certificates are available on request. \*This guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee, please contact your GH Commercial Account Manager or our Head Office.