

Regent 1200



TECHNICAL SPECIFICATIONS

Country of Origin:	South Korea	Colours:	12 Standard
Total Product Thickness:	2.5mm	Hard Flooring Size:	178mm x 1219mm
Installation Method:	Direct Stick	Type:	Vinyl Plank Flooring
Wear Layer:	0.5mm	Units Per Box:	18 boards
m ² per box:	3.91	m ² per pallet:	215.05
Finish:	Matte	Surface:	Embossed
Profile:	Square Edge	Protective Coating:	PUR
Quickship AU:	Emmet, Longreach, Brokenhill, Cobar, Birdsville, Georgetown, Melrose, Charleville, Burke, Silverton, Winton	Quickship WA:	Emmet, Longreach, Brokenhill, Cobar, Birdsville, Georgetown, Melrose, Charleville, Burke, Silverton, Winton, Stamford

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 8.1kW/m ² With Underlay: (EN ISO 9239) CRF 8.4kW/m ²
Colourfast to light:	(EN ISO 105-B02) 6-7
Light Reflectance:	105 - 42.44 180 - 11.05 300 - 22.14 350 - 13.58 380 - 13.05 545 - 19.96 550 - 14.12 555 - 16.23 560 - 19.50 700 - 39.08 740 - 25.84 790 - 13.49
Contract Guarantee:	Available on request*
Smoke Value:	Direct Stick: (EN ISO 9239) 135% minutes With Underlay: (EN ISO 9239) 179% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: 0.05%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P5
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Thermal Conductivity:	TBA

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Green Star:	Environmental Certification Scheme (ECS). Level 1 Certificate #ECSR04
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



0.5mm Wear Layer



Matte Finish



Green Building Council



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Affordable

Regent 1200



Colour Variation



Waterproof Surface



Waterproof Core




Waterproof


Regent 1200




105
Emmet



180
Longreach




300
Brokenhill




350
Cobar




380
Birdsville




545
Georgetown



550
Melrose



555
Charleville



560
Burke



700
Silverton



740
Winton



790
Stamford

Regent 1200



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst vinyl plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.