Sandstone R10

TECHNICAL SPECIFICATIONS

Country of Origin:	China
Total Product Thickness:	2mm
Notes:	Matching Heat Welds Available. See documents tab for more information.
Wear Layer:	0.7mm
Surface:	Embossed
Roll Width:	Width: 2m, Length: 20m

Colours:	4 Standard
Installation Method:	Direct Stick
Type:	Vinyl Sheet Flooring
Finish:	Matte
Protective Coating:	Embossed
Seaming Method:	Matching Heat Welds Available

PERFORMANCE

Contract Guarantee:	Available on request*
Slip Resistance:	(AS 4586) P4, R10
Recommended Adhesive:	See Adhesive Recommendations Flyer in the Documents tab above.

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



Homogeneous Vinyl Sheet



2m Wide


Water Resistant



Affordable



Direct Stick




ISO 9001 Quality Management System




ISO 14001 Environment Management System

Sandstone R10



300
Pumice



500
Quartz



760
Ironsand



790
Coal

Sandstone R10

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial vinyl sheet products must be installed in accordance with relevant Australian Standards and in conjunction with the GH Commercial Vinyl Sheet Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.