Step Up II Walk Off Tile

TECHNICAL SPECIFICATIONS

Country of Origin:	USA
Yarn:	Duracolor® Solution Dyed Nylon
Gauge:	25.2/10cm (5/32nd Gauge)
Pile Height:	3.6 (+/- 1.0)mm
Backing:	EcoFlex NXT
Installation Method:	Quarter Turn, Ashlar, Brick, Monolithic, Multi Directional
Units Per Box:	14
Pattern Repeat:	Not Applicable

Colours:	1 Standard
Surface Texture:	Performance Tip Shear
Total Product Thickness:	6 (+/- 1.0)mm
Pile Weight:	1288.00 g/m² (38 oz)
Carpet Tiles & Planks Size:	609.6mm x 609.6mm
Type:	Carpet Tiles and Planks
m² per box:	5.2

PERFORMANCE

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	ASTM E 648 Class 1 (Glue Down)~
Light Reflectance:	Available on Request
Stain Resistance:	Duracolor® Tricor - Permanent, Built into fibre
Contract Guarantee:	15 Years Available on Request*
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Soil Resistance:	EcoSentry Soil Treatment
Foot traffic recommendation tarr:	Severe

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	CRI Green Label Plus GLP1171
Environmental Product Declaration:	EPD EcoFlex NXT
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Duracolor® TriCor SDN

PVC Free

CRI

Green Building Council

ISO 9001 Quality Management System

ISO 14001 Environment Management System

Cut and Loop Pile

Premium

Declare® Red List Free

Step Up II Walk Off Tile



983

Iron Ore

Step Up II Walk Off Tile

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.
Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear.
Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.
~Test results and certificates are available on request.
*Guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.