Texmark

TECHNICAL SPECIFICATIONS

Country of Origin:	Belgium
Total Product Thickness:	2.80mm
Notes:	^Subject to proper installation and maintenance. Not suitable for areas with floor drains or excessive moisture/ flooding.
Wear Layer:	0.7mm
Surface:	Embossed
Roll Width:	Width: 4m, Length: 30m

Colours:	18 Standard
Installation Method:	Direct Stick
Type:	Vinyl Sheet Flooring
Finish:	Matte
Protective Coating:	PUR Lacquer

PERFORMANCE

Flammability:	Direct Stick: CRF – 5.7 kW/m2 & Smoke Value 124%.min
Contract Guarantee:	Available on request*
Slip Resistance:	P3
Recommended Adhesive:	See Adhesive Recommendations Flyer in the Documents tab above.

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Heterogenous Vinyl Sheet



4M


Water Resistant



Affordable



Direct Stick



ISO 9001 Quality Management System



ISO 14001 Environment Management System

Texmark

COMMERCIAL



180
Harvey Tan



300
Patagonia Light



325
Duke Natural



505
Denia Light



510
Lumber Neutral



530
Bari Sand



535
Copenhagen Mid



540
Patagonia Honey



545
Blackbutt Summer



546
Blackbutt Classic



555
Spotted Gum Coastal



556
Spotted Gum Almond



560
Copenhagen Warm



705
Duke Grey




725
Padua Granite



730



780



795

Godfrey Hirst

General Enquiries: 1300 300 821
ghcommercial.com

Texmark

COMMERCIAL

Denia Ash Bari Stone Denia Dusk

Texmark

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial vinyl sheet products must be installed in accordance with relevant Australian Standards and in conjunction with the GH Commercial Vinyl Sheet Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.