Uplifting Others

TECHNICAL SPECIFICATIONS

Collection:	Social Canvas
Colours:	8 Standard
Surface Texture:	Patterned Textured Loop Pile
Total Product Thickness:	6.5 (+/- 1.0)mm
Pile Weight:	848.00 g/m² (25 oz)
Carpet Tiles & Planks Size:	304.8mm x 914.4mm
Type:	Carpet Tiles and Planks
m² per box:	3.902
Pattern Repeat:	Not Applicable

Country of Origin:	Australia
Yarn:	Duracolor® Solution Dyed Nylon
Gauge:	47/10cm (1/12th Gauge)
Pile Height:	4 (+/- 1.0)mm
Backing:	Enviro Bac®
Installation Method:	Half-Lap, Plank Half-Lap, Brick Ashlar, Random, Herringbone, Basket Weave
Units Per Box:	14
m² per pallet:	105.35

PERFORMANCE

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for flooring in Class 2-9 buildings~
Colourfast to light:	(ISO 105-B-02-1994) 6-7
Light Reflectance:	Available on Request
Stain Resistance:	Duracolor® Tricor - Permanent, Built into fibre
Contract Guarantee:	15 Years Available on Request*
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS) Level 4+. Achieves 12+ Points meeting Best Practice Requirements - Certificate #23354
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.

AVAILABILITY

Backing Options:	Enviro Bac Plus® cushion backing, Enviro Bac Lite® cushion backing

Australian Made

SDN Carpet Tiles and Planks on Enviro Bac and Enviro Bac Plus

ISO 9001 Quality Management System

ISO 45001 OHS Management System

ISO 14001 Environment Management System

PVC Free

Uplifting Others

Green Building Council

Duracolor® TriCor SDN

Patterned Textured Loop Pile

Premium

Declare® Red List Free


ECS Level 4+

Pattern Perfect Carpet Tile with Enviro Bac®

Uplifting Others




535
Flow State




729
True Self




829
Journal




935
Creative Soul



936
Fresh Paint



937
Gallery



938
Portrait



989
Portfolio

Uplifting Others

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.
Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear.
Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.
~Test results and certificates are available on request.
*Guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.