

## TECHNICAL SPECIFICATIONS

|                            |  |                          |                               |
|----------------------------|--|--------------------------|-------------------------------|
| Country of Origin:         | Australia                                      | Colours:                 | 5 Standard                    |
| Yarn:                      | 100% Statron Plus® Solution Dyed Nylon         | Surface Texture:         | Patterned Textured Loop Pile  |
| Gauge:                     | 47/10cm (1/12th Gauge)                         | Total Product Thickness: | 6 (+/- 1.0)mm                 |
| Pile Height:               | 3.5 (+/- 1.0)mm                                | Pile Weight:             | 610.00g/m <sup>2</sup> (18oz) |
| Backing:                   | Enviro Bac®                                    | Size:                    | 250mm x 1000mm                |
| Installation Method:       | Herringbone, Ashlar, Half-Lap, Plank Half-Lap, | Type:                    | Carpet Tiles and Planks       |
| Units Per Box:             | 20   | m <sup>2</sup> per box:  | 5                             |
| m <sup>2</sup> per pallet: | 180  | Quickship AU:            | Taupe, Silver, Charcoal       |
| Quickship QLD:             | Cornflower, Iron, Charcoal                     |                          |                               |

## PERFORMANCE

|                         |  |
|-------------------------|--|
| Anti-Static:            | (AATCC 134) <math>\leq 3.5KV</math> at 21°C & 20% Relative Humidity                                      |
| Flammability:           | Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for Class 2-9 buildings~    |
| Light Reflectance:      | Available on Request   |
| Stain Resistance:       | Stain Warden®  |
| Biocontaminant Control: | Bioshield® Antimicrobial Control   |
| ACCS Rating:            | Contract Extra Heavy Duty - 4 Star   |
| Recommended Adhesive:   | Refer to our GH Commercial Adhesive Guide <a href="http://www.ghcommercial.com">www.ghcommercial.com</a> |

## SUSTAINABILITY

|                                    |   |
|------------------------------------|---|
| PVC Minimisation:                  | PVC Free  |
| Indoor Air Quality:                | Green Building Council Compliant for VOC emission rate limits   |
| Product Transparency:              | Declare Red List Free   |
| Environmental Product Declaration: | Environmental Product Declaration in accordance with ISO 14025 and EN 15804+A2  |
| Green Star:                        | Environmental Certification Scheme (ECS) Level 4+. Achieves 12+ Points meeting Best Practice Requirements - Certificate #23379  |
| Accreditation:                     | Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies. |

## AVAILABILITY

|                  |  |
|------------------|--|
| Size Options:    | 500mm x 500mm carpet tile  |
| Backing Options: | Enviro Bac Plus® cushion backing, Enviro Bac Lite® cushion backing |

# Visual Connections



Australian Made



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Contract Extra Heavy Duty - 4 Star



Green Building Council



Statron Plus® SDN



Patterned Textured Loop Pile



PVC Free



Declare® Red List Free



SDN Carpet Tiles and Planks on Enviro Bac and Enviro Bac Plus



Mid Range




Environmental Product Declaration




ECS Level 4+


# Visual Connections




535  
Cornflower




859  
Taupe



929  
Silver



969  
Iron



989  
Charcoal

# Visual Connections



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

#### Manufacturing Standards:

All specifications and colours are subject to manufacturing tolerances and may be changed or discontinued without notice. Product images are for reference only; actual colours may vary from samples due to printing variations, dye lot differences, production runs, and lighting conditions. All variations are within industry standards.

#### Natural Product Characteristics:

Depending on style and fibre, commercial carpet tiles, planks, and broadloom may develop natural characteristics over time:

**Tile-to-Tile Variation:** Commercial carpet tiles and planks may display natural variations in colour, texture, and pattern between individual tiles or planks. These variations are inherent characteristics of the product and do not constitute a manufacturing defect.

**Permanent Pile Reversal/Shading:** Cut pile and cut-and-loop carpets may appear lighter or darker in different areas of the same installation (also called watermarking or pile reversal). This is an inherent characteristic of these carpet styles and does not constitute a manufacturing defect.

**Tracking:** Footprint impressions may occur on plush cut pile surfaces, especially in high-traffic commercial areas. Vacuuming removes these marks, though they may reappear with use.

**Other characteristics:** Panelling, shift lines, or phasing may develop depending on carpet style and fibre.

#### Pattern Matching:

Patterned carpet tiles and planks naturally vary in size and appearance. Skilled installers will achieve close pattern alignment in most cases, though exact matches cannot be guaranteed.

#### Installation:

All GH Commercial carpet tiles, planks, and broadloom carpets must be professionally installed following AS/NZS 2455.1:2007 standards and relevant GH Commercial Installation Instructions. Proper subfloor preparation, moisture testing, and adhesive application are essential for product performance and warranty validation.

#### Maintenance:

Regular vacuuming and periodic professional cleaning are essential to maintain appearance and performance. Chair pads are recommended under office chairs with roller castors to preserve appearance retention, prevent delamination, and avoid premature wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling. Refer to specific maintenance guidelines for your product to ensure optimal performance in commercial environments.

#### Warranty:

All GH Commercial carpet products carry a warranty supported by New Zealand after-sales service. Commercial warranties are provided in addition to any rights consumers may have under New Zealand consumer law and are issued on a project-by-project basis with specific terms and conditions.

For detailed warranty information, installation guidelines, care instructions, and product characteristics, visit [www.ghcommercial.com](http://www.ghcommercial.com) or call 0800 500 210. For project-specific warranty enquiries, contact your GH Commercial Account Manager.

Test results and certificates available on request.