

Zenith 1800



TECHNICAL SPECIFICATIONS

Colours:	12 Standard	Total Product Thickness:	10mm
Backing:	1.5mm Acoustic Backing	Hard Flooring Size:	225mm x 1800mm
Installation Method:	Uniclic®	Type:	Hybrid Flooring
Wear Layer:	0.5mm	Units Per Box:	4 boards
m ² per box:	1.62	m ² per pallet:	84.24
Finish:	Super Matte	Surface:	Embossed in Register
Profile:	Micro Bevel	Substrate Layer:	Aerated Core - Trigon Acoustic M-Core
Top Layer:	Decorative Film & Wear Layer	Protective Coating:	PUR
Quickship AU:	Nebula Walnut, Cosmic Sand, Aurora Pine, Stellar Oak, Celestial Driftwood, Prime Blackbutt, Galactic Grove, Astral Slate, Eclipse Shadow		

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 10.2kW/m ²
Light Reflectance:	110 - 31.09 120 - 27.75 190 - 16.94 300 - 31.01 325 - 27.62 350 - 18.33 365 - 19.34 545 - 25.46 555 - 17.12 560 - 12.90 740 - 12.97 795 - 13.70
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 105% minutes
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P5



Micro Bevel Edge



Embossed in Register



Matte Finish



Mid Range



ISO 9001 Quality Management System



ISO 14001 Environment Management System



0.5mm Wear Layer


Zenith 1800




110
Solar Drift



120
Lunar Ash



190
Nebula Walnut




300
Cosmic Sand




325
Aurora Pine



350
Stellar Oak




365
Celestial Driftwood



545
Prime Blackbutt




555
Starry Spotted Gum



560
Galactic Grove



740
Astral Slate



795
Eclipse Shadow

Zenith 1800



Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^ Subject to proper installation, maintenance and local building code/regulatory approval.